

ADDENDUM NO. 1

WEST VALLEY SANITATION DISTRICT
OF SANTA CLARA COUNTY, CALIFORNIA
100 East Sunnyoaks Avenue
Campbell, California 95008

2022 OK CHAMPION CONTINUOUS RODDER

The following are items that modify and or clarify the specification requirements of the OK Champion Continuous Rodder Request for Bids dated, July 21, 2021.

SECTION I – OK CHAMPION RODDER

Operator Control Station (P.3)

8. Control Panel Lighting: All controls and instrumentation on the control panel must be fully illuminated and readable at night. Provide two switched external (weatherproof) LED lights at the top or above the panel and shielded to prevent direct light into operator's eyes. **Alternate lighting options may be submitted to District for approval.**

Truck Bed (P..5)

Two 4-inch D-rings shall be installed on the lower part of the rear bumper just outside of each leg of the A-frame rod hose support (~~Ref. Picture B~~). **The A-Frame and Hose Guide Bracket are described as:**

- 1. Hose support and clamp, A-frame style attached at rear below hose guide. Unit shall be constructed of solid stock steel. (See Picture B.1 – A Frame).**
- 2. Fabricate & install hose guide bracket 3" diameter x 6" long pipe with adjustable t-handle screws. This shall be mounted to an appropriately sized channel iron 12" long which shall butt up against the rod guide. The distance between the rod guide and the bracket shall be no more than 6.5-inches. (See Picture G – Hose Guide Bracket).**

Toolboxes (P.6)

All toolbox compartment doors are to be weather sealed and leak proof. All compartment doors shall have chromed T-handle 3-point locking mechanisms with barrel locks, all keyed alike, and set in stainless steel lock pockets (Ref. Picture C). Doors shall use one piece rolled hinge with 5/16" stainless steel rod. **If no comparable one piece rolled hinges are available, chrome strap hinges may be substituted with District prior approval.** All toolbox interiors shall be illuminated (see Lighting and Camera). Install drip channel above each toolbox door. Perform water spray test on entire unit to confirm seals and all connected components are leak proof.

Lighting and Camera (P.7)

2. Two (2) 4" round Whelen TIR6 Super-LED (2FC00ZCR/2FLANGEC) lights to illuminate the interior housing of the cowling. One light mounted over the reel area and the other over the drive head area with a single switch **with "ON" indicator lamp** installed on control panel.

3. One (1) white Whelen Pioneer Plus with handle and locking pedestal mount (PFH1PH/PBAPEDDL) mounted on top of a painted steel fabricated mount (rear camera to be mounted below the work light). Switch for worklight **with "ON" indicator lamp** shall be installed on operator control panel.

5.e. Two (2) Micro Freedom Super LEDs (MCFLED2A) mounted on top of the Peterbilt provided cab mounts over each door. **Mounts are to be provided by Peterbilt.**

5.f. Pro-Vision Model TV-505A **back-up** camera system with 7" color monitor mounted on dash within easy view of the driver and wire unit through a factory OEM on/off switch on the dash **(and not be tied to reverse switch)**. Camera to be installed below rear work light on fabricated mount.

6. Toolbox Lighting: Install Whelen Fluorent Plus Super-LED tube lighting in all toolboxes. Tubes to run length of toolbox above each compartment space (upper and lower shelves). Place master switch **in cab with "ON" indicator lamp on Operator Control Panel . Place all three lighting control panel switches in grouped horizontal alignment.**

Accessories (P.8)

1. Install a 3000W inverter and provide two exterior GFCI power outlet boxes at the rear of the rodder. One 120V outlet to be installed on the driver's side above the rear bumper area and the other on a vertical wall directly below the operator control panel. **The 3000W Inverter will run off of 200A truck alternator and 3 battery set.**

3. Delete ~~Install two (2) 4" diameter steel pipe.~~

SECTION II – PETERBUILT TRUCK CHASSIS AND CAB

Engine & Equipment (P.9)

4. ~~Two~~ **Three (3)** PACCAR Premium 12V Starting Batteries 2000 CCA.

Tires, Wheels & Suspension (P.9)

1. ~~Michelin~~ **Bridgestone** 16 ply radial 295/75R22.5 tires. Rear tires to be mud and snow rated.
4. ~~Jake/engine break~~ **VGT Exhaust Brake.**

Cab & Equipment (P.10)

2. Air Ride (UltraRide) high back seats for driver. **Non-Air Ride high back vinyl passenger seat.**

Extended Warranty (P.10)

In addition to the Peterbilt Class ~~76~~ Standard Coverage (1yr/unlimited miles) and PACCAR PX-7 Standard Coverage (3 years/unlimited miles) provide the following extended coverages.

1. 5 year or 150,000 mile **extended** warranty on the engine and exhaust aftertreatment.
2. 5 year/ ~~Allison~~ **unlimited miles extended** transmission warranty.

Paint (P.10)

3. Front bumper shall be **black chrome or painted white.**

SECTION III – SPECIAL CONDITIONS

Warranty (P.11)

1. All warranties shall begin **from the day the rodder is placed in service, no later than 60 days after-upon** the District's acceptance of the completed OK Champion Rodder after delivery to the District facility and after all requirements have been satisfied (full acceptance by the District).



Picture B.1
A – Frame



Picture G
Hose Guide Bracket